



Product code : 076000

EMFILATEX 760

DESCRIPTION

Natural latex based adhesive.

AREAS OF APPLICATION

EMFILATEX 760 is used in shoe and leather industry especially for fast bonding of fabric, felt, cardboard or leather.

TECHNICAL DATA

Colour	White (glue)	Colourless (film)
Viscosity	Brookfield LVT / spindle 1 / 12 rpm : 125 ± 25 mPa.s (may increase somewhat with time)	
Density at 20 °C	0.945 ± 0.015	
Conventional solids content (EN 827)	62.5 ± 2.5 %	
Open time at 20 °C	5 to 10 min according to materials	
Cleaner	Water	
Specific data	Film properties : very elastic and flexible Initial setting : immediate	

ADVICE

See also material safety data sheet

INSTRUCTIONS FOR USE

Substrates preparation :

The substrates to be assembled must be dust free and not have any traces of grease or other contaminants that could adversely affect the bonding performance.

Application :

Coat each substrate with a regular layer of EMFILATEX 760 with a brush, a roller or a spray gun on each substrate. Apply precisely both parts immediately or before the end of open time and press briefly but firmly. The immediate setting is good, and very high in case of bonding leather to itself.

STORAGE AND SHELF LIFE

12 months between 5 and 25 °C in closed original packaging.

PACKAGING

1 kg boxes ; 5 L cans ; 25 kg buckets

SAFETY

Not classified as hazardous. Read material safety data sheet.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.