



Product code : 086301E052

EMFIPARQUET RL

DESCRIPTION

EMFIPARQUET RL is a fast setting single component water-based vinyl adhesive.

AREAS OF APPLICATION

EMFIPARQUET RL is specially designed for bonding hardwood flooring together at tongue and groove when laying a floating floor system.

TECHNICAL DATA

Colour	White
Viscosity	Brookfield RVT / spindle 6 / 20 rpm : 12,500 ± 3,500 mPa.s
Density at 20 °C	Ca 1.10
pH	Ca 3
White point	Ca +5 °C
Application temperature	10 to 25 °C (adhesive and substrates)
Cold resistance	Down to -30 °C
Open time at 20 °C	6 to 10 min
Final setting at 20 °C	24 h
Cleaner	Water before setting

ADVICE

See also material safety data sheet



INSTRUCTIONS FOR USE

Substrate preparation :

Wood panels must be even, clean, dry, free of dust and grease.

Do not work at temperatures below +10 °C or when the relative humidity exceeds 65 %.

If necessary, heat and ventilate the room.

The humidity of the parquet flooring should be between 7 and 11 %.

Application :

Apply EMFIPARQUET RL with the feeding bottle nozzle on the top groove edge in a discontinuous line on lath or panel length.

Fit the panels together tightly to assure maximum adhesive distribution and adequate bond during the 10 following minutes.

Leave a free space of 10 to 20 mm all around the room.

Wipe off any excess adhesive that has been squeezed out between the joints.

Allow to dry for at least 48 hours before sanding.

Cleaning :

Excess adhesive, smudges and tools can be cleaned with water before drying.

CONSUMPTION

1 bottle of 500 g allows bonding of 65 to 100 linear meters.

STORAGE AND SHELF LIFE

12 months in hermetically sealed original packaging stored between 5 and 25 °C.

PACKAGING

500 g plastic bottles.

SAFETY

Not classified as hazardous. Read material safety data sheet.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.