



Product code : 30040D

EMFICOL 30040D

DESCRIPTION

EMFICOL 30040D is a contact adhesive based on polychloroprene rubber and reactive synthetic resins in organic solvents.

AREAS OF APPLICATION

EMFICOL 30040D can be used for bonding rubber slabs, PVC, cork or linoleum to usual building substrates.

TECHNICAL DATA

Colour	Light brown
Viscosity	Brookfield RVT / spindle 3 / 20 rpm : 2,500 ± 250 mPa.s
Density at 20 °C	0.88 ± 0.01
Conventional solids content (EN 827)	23 ± 1.5 %
Application temperature	15 to 30 °C
Cleaner	EMFINET 695

ADVICE

See also material safety data sheet



INSTRUCTIONS FOR USE

Substrates preparation :

The substrates to be assembled must be dry, dust free and not have any traces of grease or other contaminants that could adversely affect the adhesive performance.

Extinguish all sources of ignition and carefully follow the safety and handling instructions given by the manufacturer.

Application :

Apply a regular layer with a brush or a notched spreader to each substrate.

Let solvents evaporate during 20 to 30 minutes.

Assemble precisely both parts and press briefly but firmly and evenly on the whole surface.

Once the two substrates are assembled, they can't be repositioned or separated.

In damp and cold weather, ensure that materials and adhesive are at a correct temperature (over 15 °C) in order to prevent formation of dew as the solvents evaporate, which could result in defective bonding.

CONSUMPTION

150 to 225 g/m² to each surface depending on substrates.

STORAGE AND SHELF LIFE

12 months between 5 and 25 °C in closed original packaging.

PACKAGING

Metal packagings

SAFETY

Highly flammable and harmful. Read material safety data sheet before use.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.