



Product code : 34011A

SAPOCOL GP 2001 TRANSPARENT

DESCRIPTION

SAPOCOL GP 2001 TRANSPARENT is a primer containing isocyanates.

AREAS OF APPLICATION

SAPOCOL GP 2001 TRANSPARENT may be used on different substrates (concrete, aluminium, wood, glass, plastics) to improve the adhesion of PU sealants.

Seals off the porosity of materials such as wood or concrete, thus reducing or preventing problems of bubbling under severe conditions.

May also be used as a barrier between sealant and paint to prevent migration of plasticizers.

TECHNICAL DATA

Colour	Pale yellow transparent
Viscosity	Brookfield RVT spindle 2 / 100 rpm : 45 ± 15 mPa.s
Density at 20 °C	Ca 0.92
Conventional solids content (EN 827)	25 ± 3 %
Application temperature	5 to 40 °C
Specific data	Drying time : 10 to 15 min

ADVICE

See also material safety data sheet

INSTRUCTIONS FOR USE

Substrate preparation :

The substrates to be assembled must be dry, dust free and not have any traces of grease or other contaminants that could adversely affect the bonding performance.

If the substrates need to be cleaned, solvents such as EMFINET 683, methylethylketone (MEK) or acetone may be used. For substrates sensitive to ketones, use EMFINET 688/1.

The use of solvents must comply with local regulations. Check the compatibility of the solvent used with the substrates.

If necessary, rub down metal surfaces beforehand. After rubbing down, the surface should be re-cleaned. Allow the substrate to dry after degreasing. We recommend that concrete be cleaned with a metal brush.

Note : when using solvents, extinguish all sources of ignition and carefully follow the safety and handling instructions given by the manufacturer or supplier.

Application :

SAPOCOL GP 2001 TRANSPARENT may be applied by a lint-free applicator pad or brush between 5 and 40 °C. Thoroughly homogenise before application.

This product should be used within 24 hours of opening the protective seal on the bottle. Close after every use (any contact with moisture will cause the product to cure).

If applied in cold weather, store the packagings at 20 °C before use.

After drying, apply the sealant within a one hour deadline, proceeding according to instructions of its technical data sheet.

Cleaning :

Tools should be cleaned with EMFINET 683, MEK or acetone before the sealant has completely cured. After curing, abrasion is necessary.

STORAGE AND SHELF LIFE

12 months in the original, hermetically sealed packaging between 5 and 40 °C

PACKAGING

30 and 250 g bottles ; 1 kg cans ; 5.2 and 10 kg buckets ; 200 L drums.

SAFETY

Irritant and highly flammable. Read the material safety data sheet before use.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.