



Product code : 34025A

EMFIPRIM 34025A

DESCRIPTION

EMFIPRIM 34025A is a mixture of polyisocyanates and organic solvents.

AREAS OF APPLICATION

EMFIPRIM 34025A is a cleaning agent and primer for polyurethane sealants and MS or SPUR hybrid sealants.

TECHNICAL DATA

Colour	Yellowish transparent
Viscosity	Ca. 1 mPa.s
Density at 20 °C	0.94 ± 0.03
Conventional solids content (EN 827)	11 ± 1 %
Application temperature	15 to 30 °C
Specific data	Drying time : 10 to 15 min

ADVICE

See also material safety data sheet

INSTRUCTIONS FOR USE

Substrates preparation :

The substrates to be coated must be clean, dry, dust free and not have any traces of grease or other contaminants that could adversely affect the bonding performance.

If the substrates need to be cleaned, solution EMFINET 683, methylethylketone (MEK) or acetone may be used. Check the compatibility of the solvent used with the substrates.

When using solvents, extinguish all sources of ignition and carefully follow the safety and handling instructions given by the manufacturer or supplier.

Application :

EMFIPRIM 34025A may be coated with a felt dauber or a fluff-free cloth.

Apply a uniform and light pressure in order to get a homogenous film.

Hermetically seal the container immediately after use. Any contact with humidity will make the primer cure. For this reason, the product must be used within 24 hours after opening the bottle.

Let dry for minimum 15 min before applying the sealant.

After drying, apply the sealant within a one hour deadline, proceeding according to instructions of its technical data sheet.

STORAGE AND SHELF LIFE

- 12 months in closed original packaging stored between 0 and 35 °C

- 1 month after first opening of the bottle in closed original packaging between 0 and 35 °C

PACKAGING

30, 250 and 1,000 mL aluminium bottles

SAFETY

Harmful and highly flammable. Read material safety data sheet before use.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.