



Product code : 34029C

EMFIPRIM PU MONO

DESCRIPTION

EMFIPRIM PU MONO is a single component polyurethane based primer which cures under the effect of ambient moisture.

AREAS OF APPLICATION

EMFIPRIM PU MONO can be used as adherence primer on porous or on non-porous and smooth materials (ceramic tiles, adherent and cohesive paints, traces of old glues, etc.) before screeding or application of parquet adhesive.

Applied in two cross layers, EMFIPRIM PU MONO can also be used for waterproofing of absorbent surfaces.

EMFIPRIM PU MONO can be applied on concrete screeds containing up to 5 % relative humidity.

Doesn't fit on bituminous subfloors.

TECHNICAL DATA

Colour	Brown
Viscosity	Brookfield LVT / spindle 2 / 12 rpm : ca. 600 mPa.s
Density at 20 °C	1.12
Specific data	Drying time at 23 °C and 50 % RH : ca. 1 h

ADVICE

See also material safety data sheet

INSTRUCTIONS FOR USE

Substrate preparation :

The substrates must be sound, free of splits, dust, grease or other contaminants that could affect adhesion.

RUBBING DOWN IS NECESSARY BEFORE APPLICATION ON SMOOTH AND NON POROUS SUBSTRATES.

Application :

Do not work under 10 °C.

Apply EMFIPRIM PU MONO with a roller.

If used for waterproofing, apply a second layer after full drying.

Sanding is not necessary.

Continue working only after full drying (maximum 48 h after application).

Cleaning :

Tools can be cleaned with EMFINET 683, methylethylketone (MEK) or acetone before primer has completely cured.

After curing, abrasion is necessary.

CONSUMPTION

250 to 350 g/m² according to substrates

STORAGE AND SHELF LIFE

6 months in hermetically sealed original packaging between 5 and 25 °C

PACKAGING

5 kg metal buckets

SAFETY

Harmful. Read the material safety data sheet before use.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.