



Product code : 36014B

EMFICOL 36014B

DESCRIPTION

High dry content sprayable adhesive based on synthetic polymers and resins in organic solvents of low odour.

AREAS OF APPLICATION

EMFICOL 36014B is used for quick bonding of foams made of polyester, polyether and latex between themselves or on different substrates like cardboard, particle board, wood, polyester.

It is recommended for one-way application.

TECHNICAL DATA

Colour	Light yellow
Viscosity	Brookfield LVT / spindle 1 / 30 rpm : 80 ± 10 mPa.s
Density at 20 °C	0.85 ± 0.03
Conventional solids content (EN 827)	42.5 ± 2.5 %
Open time at 20 °C	One-way : 1 to 10 min Two-way : 1 h
Temperature resistance of the assemblies	Ca 60 °C
Cleaner	EMFINET 695
Specific data	Freezing resistance : reversible thickening

ADVICE

See also material safety data sheet



INSTRUCTIONS FOR USE

Substrates preparation :

The surfaces must be clean, dry and free of grease.

Application :

Apply with a manual or an automatic spray gun (nozzle diameter : 1.5 to 2 mm ; air pressure : 3 to 5 bar ; product pressure : 1 to 1.5 bar).

One-way application is sufficient. Spraying must be very fine, assembling can be done quite immediately with a uniform and short strong pressure applied on the entire surface.

The high tack and good heat resistance of EMFICOL 36014B allows assemblies under strain.

The best application temperature is between 15 and 25 °C.

CONSUMPTION

150 to 250 g/m² for one-way application.

90 to 130 g/m² for two-way application.

STORAGE AND SHELF LIFE

12 months between 5 and 25 °C in closed original packaging.

PACKAGING

25 L cans, 200 L drums and 1 000 L containers.

SAFETY

Highly flammable and irritant. Read material safety data sheet before use.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.