



Product code : 36015A

EMFICOL 36015A

DESCRIPTION

EMFICOL 36015A is an adhesive based on synthetic rubber and resins dissolved in organic solvents.

AREAS OF APPLICATION

EMFICOL 36015A is used for bonding insulating elements (expanded or extruded polystyrene , polyurethane foam, mineral wool) on metal, wood or plaster boards.

TECHNICAL DATA

Colour	Red
Viscosity	Brookfield RVT / spindle 3 / 20 rpm : 1,500 ± 250 mPa.s
Density at 20 °C	0.80 ± 0.03
Conventional solids content (EN 827)	27.5 ± 2.5 %
Application temperature	15 to 25 °C
Open time at 20 °C	Ca. 30 min
Temperature resistance of the assemblies	Ca. 70 °C
Cleaner	EMFINET 688/1

ADVICE

See also material safety data sheet



INSTRUCTIONS FOR USE

Substrates preparation :

The substrates to be assembled must be dry, dust free and not have any traces of grease or other contaminants that could adversely affect the adhesive performance.

They may be cleaned with EMFINET 683, methylethyketone (MEK) or acetone.

When using solvents, extinguish all sources of ignition and carefully follow the safety and handling instructions given by the manufacturer.

Application :

Apply with a brush to both substrates.

Assemble after a drying time of 5 to 10 minutes.

Take care not to exceed open time ; otherwise, bonding will be defective.

Assemble precisely both parts and press firmly and evenly on the whole surface in order that both surfaces remain in full contact.

CONSUMPTION

100 to 200 g/m² to each surface

STORAGE AND SHELF LIFE

12 months between 5 and 25 °C in closed original packaging

PACKAGING

5 and 25 L metal cans
200 L drums

SAFETY

Highly flammable and irritant. Read material safety data sheet before use.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.