



Product code : 36018A

EMFICOL 36018A

DESCRIPTION

Sprayable adhesive based on polymeric synthetics in organochloric solution.

AREAS OF APPLICATION

This sprayable glue with a high solids content is used for bonding of foams made of polyester, polyether and latex between themselves or on different supports like cardboard, particle board, polyester… It is recommended for one way bonding.

TECHNICAL DATA

Colour	Red
Viscosity	Brookfield LVT / spindle 2 / 30 rpm : 230 ± 30 mPa.s
Density at 20 °C	1.20 ± 0.01
Conventional solids content (EN 827)	39.5 ± 2.5 %
Application temperature	15 to 25 °C
Open time at 20 °C	One-way : 1 to 10 min Two-way : 1 to 35 min
Temperature resistance of the assemblies	Ca 70 °C
Cleaner	EMFINET 692

ADVICE

See also material safety data sheet



INSTRUCTIONS FOR USE

The surface must be clean, dry and free of grease.

Apply with a manual or an automatic-spray gun (1.5-2 mm; pressure 3 to 5 bar ; material pressure 1 to 1.5 bar).

One way application is sufficient, the spraying must be very fine, the contact can be made immediately using a short strong pressure.

The spraying of this glue is very fine and allows to save time and product, obtaining bondings with high mechanical resistance and high heat resistance. A very high tack allows bondings under strain.

CONSUMPTION

150 to 200 g/m² for one way application.

90 to 130 g/m² for double way application.

STORAGE AND SHELF LIFE

6 months between 5 and 25 °C in closed original packaging.

PACKAGING

Varnished metal containers : 750 mL boxes, 6 and 29 kg cans, 240 kg drums.

SAFETY

Harmful. Read material safety data sheet before use.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.