



Product code : 36029B

EMFICOL 36029B

DESCRIPTION

EMFICOL 36029B is a sealant based on synthetic elastomers and resins in organic solvents.

AREAS OF APPLICATION

EMFICOL 36029B can be used for bonding a lot of materials : wood, metal, usual building insulating materials (mineral wool, polyurethane panels), decorative ceiling roses and cornices on porous or non-porous substrates.

EMFICOL 36029B cannot be used for bonding expanded or extruded polystyrene.

TECHNICAL DATA

Colour	Dark beige
Viscosity	Brookfield HBT/spindle E/ 5 t/min: 1,600 000 ± 300,000 mPa.s
Density at 20 °C	1.20 ± 0.03
Conventional solids content (EN 827)	72 ± 3 %

ADVICE

See also material safety data sheet

INSTRUCTIONS FOR USE

Substrates preparation :

The substrates must be even, clean, dry, free of grease, dust free and not have any traces of other contaminants that could adversely affect the bonding performance.

They may be cleaned with EMFINET 695, or EMFINET 688/1 for surfaces sensitive to ketones.

Check the compatibility of the solvent used with the substrates.

If necessary rub down the metallic surfaces. Clean them after rubbing down. Let dry after degreasing.

When using solvents, turn off all sources of ignition, follow site security rules and instructions for use.

Temperature of adhesive and substrates have to be between 15 and 30 °C.

Application :

Coating can be done with a notched spreader or in dots (notched spreader : smooth surfaces ; dots : irregular surfaces). Coat the material and put in contact with the substrate in order to transfer the adhesive. Separate to let the solvents evaporate. Check if transfer is correct.

After 10 min maximum at 20 °C, apply and press firmly. Bonding is definitive.

CONSUMPTION

300 to 600 g/m²

STORAGE AND SHELF LIFE

12 months between 15 and 20 °C in closed original packaging

PACKAGING

310 ml cartridges

SAFETY

Highly flammable and harmful. Read material safety data sheet before use.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.