



Product code : 38050A

PRIMAIRE 38050A

DESCRIPTION

PRIMAIRE 38050A is an alcoholic solution of polysilanes.

AREAS OF APPLICATION

PRIMAIRE 38050A improves adhesion of polyurethane sealants on difficult surfaces, especially on raw or anodized aluminium, or on galvanized steel, PVC, glass...

TECHNICAL DATA

Colour	Colourless
Viscosity	Extremely low (ca. 1 mPa.s)
Density at 20 °C	0.80
Conventional solids content (EN 827)	1.5 ± 0.5 %
Application temperature	5 to 40 °C

ADVICE

See also material safety data sheet

INSTRUCTIONS FOR USE

Substrates preparation :

The substrates to be assembled must be clean, dry, dust free and not have any traces of grease or other contaminants that could adversely affect the adhesion performance.

Application :

Apply the primer with a brush or a fluff-free felt dauber in order to get a thin and regular film.

Hermetically seal the container immediately after use. This primer reacts with atmospheric moisture.

For this reason, the product must be used within 24 hours after opening the bottle.

After 10 minutes of drying, apply the sealant within a one hour deadline, proceeding according to the instructions of its technical data sheet.

STORAGE AND SHELF LIFE

12 months in hermetically closed original packaging in dry premises between 10 and 25 °C.

24 h after opening.

PACKAGING

250 and 1,000 mL bottles

SAFETY

Highly flammable and irritant. Read material safety data sheet before use.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.