



Product code : 50038B

HARDENER 50038B

DESCRIPTION

Hardener containing isocyanates

AREAS OF APPLICATION

Hardener for some two-component PU adhesives

TECHNICAL DATA

	PART A	PART B
	ISOLEMFI...	HARDENER 50038B
Type of product	Based on polyols	Based on polyisocyanates
Colour		Grey greenish
Viscosity at 20 °C		Brookfield RVT / spindle 6 / 5 rpm : ca. 17,000 mPa.s
Density at 20 °C		1.52 ± 0.03

MIXTURE A + B	
Specific data	Refer to the technical data sheet of the mixture " ISOLEMFI... + HARDENER 50038B "

ADVICE

See also material safety
data sheet



STORAGE AND SHELF LIFE

6 months in closed original packaging stored in dry premises between 5 and 25 °C

SAFETY

HARDENER 50038B (part B) is harmful. Read material safety data sheets before use.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.

