



Product code : C9819A

ACTIVATOR T

DESCRIPTION

ACTIVATOR T contains catalysts and organic solvents.

AREAS OF APPLICATION

ACTIVATOR T can be used with some EMFILOK anaerobic adhesive to increase curing rate. Use ACTIVATOR T only in the following cases :

- When the pieces are made of an inactive material (plastic), a low-activity material (stainless steel, aluminium, light alloys), or a material with an electroplated surface (zinc, chromium, etc.)
- When it is necessary to increase curing speed of anaerobic adhesives.
- When ambient temperature is very low (below 6 °C).
- When gaps between parts are closed to the limit allowed by the EMFILOK product in use.

TECHNICAL DATA

| | |
|------------------|------------------------------|
| Colour | Green, clear |
| Odor | Strong, characteristic |
| Density at 25 °C | 0.75 to 0.90 |
| Solubility | Organic solvents |
| Specific data | Appearance : volatile liquid |

ADVICE

See also material safety data sheet

INSTRUCTIONS FOR USE

Clean and dry parts using CLEANER L (ACTIVATOR T should not be used as cleaner or degreaser).

Spray a fine film of ACTIVATOR T over the surface. Let evaporate (about 30 seconds).

Apply the anaerobic adhesive. Avoid contamination of the material in the container by preventing direct contact of the application nozzle with the activated surfaces.

STORAGE AND SHELF LIFE

24 months under 25 °C in closed original packagings. Protect from direct sunlight.

PACKAGING

180 mL aerosols

SAFETY

Irritant and extremely flammable. Read material safety data sheet before use.

PRECAUTIONS FOR USE

Before applying on plastic materials or painted surfaces, check whether ACTIVATOR T causes chemical attack.

As the container is under pressure, do not expose at temperature over 50 °C.

Do not puncture or burn the container even when empty.

Do not spray the content near open flame or flammable material.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application.

Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.