



Product code : GA000

EMFIBAND

DESCRIPTION

EMFIBAND is a self-adhesive sealing strip formed of modified bitumen. One face is covered with an aluminium sheet coated or not with an epoxy paint. The other face is protected by a plastic sheet.

AREAS OF APPLICATION

EMFIBAND may be used for repairs for permanent and watertight seal on asphalt, felted bituminous roofing, glass, metals, wood, plastics, concrete, painted surfaces, clay tiles and brickworks, insulating foams.

EMFIBAND may also be used for protective wrapping and watertightening of pipes and tanks, cabin joints, glass-frames, roofings, gutters.

TECHNICAL DATA

Colour	Aluminium, grey, brick-red, ochre
Application temperature	> 5 °C
Temperature resistance	-20 to +80 °C

ADVICE

See also material safety data sheet

INSTRUCTIONS FOR USE

Substrates preparation :

Ensure surface to be coated is free from dust, oil or loose material that could adversely affect the adhesive performance. If they are porous, apply 0.2 to 0.5 liters/m² of PRIMAIRE EMFIBAND by brush or roller.

Application :

Ensure surface to be coated is free from dust, oil or loose material that could adversely affect the adhesive performance. Cut up EMFIBAND to the desired length (maximum 5 m).

Peel off the plastic sheet and apply EMFIBAND on the substrate.

Ensure about 3 cm overlapping between strips.

During laying, it is necessary to smooth the membrane with a roller from the centre to the edges to prevent formation of air pockets.

STORAGE AND SHELF LIFE

12 months between 5 and 40 °C protected from exposure to moisture.

PACKAGING

Rolls of 10 meters length and 5 - 7.5 - 10 - 12.5 - 15 - 20 - 22.5 - 30 - 45 - 60 - 100 cm widths

SAFETY

Not classified as hazardous.

Read the material safety data sheet.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.