



Product code : GZ001A

PRIMAIRE EMFIBAND

DESCRIPTION

PRIMAIRE EMFIBAND is an aqueous emulsion of bituminous materials.

AREAS OF APPLICATION

PRIMAIRE EMFIBAND is a general purpose primer recommended before laying of EMFIBAND sealing strips.

TECHNICAL DATA

Appearance	Semi-liquid gel
Colour	Black when dry
Density at 20 °C	1.18
pH	> 9.5
Conventional solids content (EN 827)	Ca 65 %
Cleaner	Water
Specific data	Cold resistance : frost sensitive Drying time : 24 h (film of 500 g/m ² at 23 °C and 55 % HR)

ADVICE

See also material safety data sheet

INSTRUCTIONS FOR USE

Substrates preparation :

Ensure surface to be coated is free from dust, oil or other contaminants that could adversely affect the adhesive performance.

Application :

Apply a thin film with a brush or a roller.

Let dry between 12 and 24 hours according to coating thickness, temperature and moisture conditions.

In case of coating on large surfaces, PRIMAIRE EMFIBAND may be diluted with 5 to 8 % of water.

STORAGE AND SHELF LIFE

12 months above 0 °C (do not expose to frost).

PACKAGING

2.5 L cans

SAFETY

Not classified as hazardous.

Read the material safety data sheet.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.