



Product code : MA009B

EMFIMASTIC TOUTJOINT N

DESCRIPTION

EMFIMASTIC TOUTJOINT N is an elastomeric sealant based on synthetic polymers in solution, setting by evaporation of the solvent to form a soft, elastic and resistant joint. EMFIMASTIC TOUTJOINT N shows an excellent resistance to weathering and mould growth.

AREAS OF APPLICATION

EMFIMASTIC TOUTJOINT N has been specially formulated for repairing roofs, gutters, for filling wood cracks, for expansion and connection joints, e.g. for roofing, facades, glass, kitchen and bathroom.


EMFIMASTIC TOUTJOINT N adheres without primer to wood, metal, glass, concrete and a lot of plastics.

TECHNICAL DATA

Appearance	Pasty
Colour	Colourless, translucent
Density at 20 °C	0.95
Conventional solids content (EN 827)	Ca. 75 %
Application temperature	5 to 40 °C
Final Shore A hardness (ISO 868 - 3 seconds)	25 ± 5
Modulus at 100 % (ISO 8339)	0.5 MPa
Smoothing time	15 to 20 min
Volume loss (ISO 10563)	Ca. 20 %
Temperature resistance	-25 to +100 °C
UV resistance	Excellent
Water and salt spray resistance	Excellent
Compatibility with paints	Water-based : yes Solvent based : test beforehand
Specific data	Hardening time : several mm/d

ADVICE

See also material safety data sheet



INSTRUCTIONS FOR USE

Substrates preparation :

The materials to be assembled may be cleaned with EMFINET 683 or methylethylketone (MEK). Check the compatibility of the solvent used with the substrates.

If necessary, rub down metal surfaces beforehand and clean them. Let dry after degreasing.
It is recommended to clean concrete with a metal brush and to degrease PVC, glass or aluminium e.g. with acetone.
When using solvents, extinguish all sources of ignition and carefully follow the safety and handling instructions given by the manufacturer.

Caulking :

EMFIMASTIC TOUTJOINT N can be applied by a manual or pneumatic gun to clean, dry and degreased substrates.
After application, use a putty knife to smooth the joint with soapy water.

Do not apply at a temperature under 5 °C. In cold weather, store the cartridges at about 20 °C before use.

Cleaning :

Tools can be cleaned with xylene, white spirit or MEK.

CONSUMPTION (for a cartridge of 310 ml)

Tube (mm)	2	3	4	5	6	7	8	9	10
Length of cord (m)	98	43	24	15	11	8	6	4	3

STORAGE AND SHELF LIFE

12 months between 5 and 25 °C in closed original packaging.

PACKAGING

310 mL cartridges

SAFETY

Not classified as hazardous. Read material safety data sheet.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.